

### HISENSE-AIR/CON 12KBTU INVERTER SPLIT-1 PHASE-COM

Model No: HNACAS12TR4RYRCA050





### **Price:**

Rs. 249,990

## Warranty:

5 Years(s) manufacturer warranty.

One-year comprehensive warranty for the entire unit against manufacturing defects. • 3 Free Service will be provided only in the 1st Year. • Five-year warranty for the compressor against manufacturing defects. • To obtain a ten-year compressor warranty, a Service Agreement must be signed with Singhagiri (Pvt) Ltd.

## **Delivery:**

Delivery - Standard 3 To 5 Working Days.

- Delivery Within 3 Working Days For Colombo And Suburbs, 5 Working Days For Other Locations.
- For Any Invoice Up To Rs.9,999, A Delivery Rate Of Rs.500 Will Be Charged.
- For Any Invoice From Rs.10,000 To 19,999, A Delivery Rate Of Rs.700 Will Be Charged.
- For Any Invoice From Rs.20,000 To 49,999, A Delivery Rate Of Rs.900 Will Be Charged.
- For Any Invoice From Rs.50,000 To 99,999, A Delivery Rate Of Rs.1200 Will Be Charged.
- For Any Invoice From Rs.100,000 To 149,999, A Delivery Rate Of Rs.1500 Will Be Charged.
- For Any Invoice From Rs.150,000 And Above, A Delivery Rate Of Rs.2000 Will Be Charged.

# **Specifications:**

- Model: AS-12TR4RYRCA00
- Type: T1, CO, Inverter
- Cooling Capacity: Btu/h 12283
- Heating Capacity: W /
- Rated Input-Cooling: W 1160
- Rated Input-Heating: W /
- Moisture Removal: L/H.r/
- Air Circulation (Indoor): m3/h 550
- Air Circulation (Outdoor): m3/h /
- CSPF for Cooling: W/W 4.6
- •
- SCOP for Heating: W/W /
- Energy Class: Heatling /
- Refrigerant: R32
- Refrigerant charge volume: g
- Indoor Unit Noise Level High: High(dB (A)) 38
- Indoor Unit Noise Level Low: Low(dB (A)) 32
- Outdoor Unit Noise Level:dB(A): 49
- Voltage, Frequency, Phase: 220-240V~,50Hz,1P
- Rated Current:Cooling (A): 5
- Rated Current: Heating (A): /
- Degree of protection (IN) / (O: (IP) IPX0/IPX4
- Class of electroprotection (IN: (I/II) CLASS I / CLASS I
- maximal pipe length: m 10
- LRA: A
- Compressor:Model No.: KSK89D59UEZC
- Compressor:MFG: GMCC
- Compressor: Expansion Device: Capillary
- Liquid Pipe inch(mm): (1/4)
- Gas Pipe inch(mm): (3/8)
- Display on Front Panel: LED
- LCD Wireless Remote Controller: Yes
- Removable and washable Panel: Yes
- Washable PP Filter: Yes
- 24 Hours Timer: Yes
- 3 Speed and Auto Indoor Fan Control: Yes
- Vertical Auto Swing Louver: Yes
- Horizontal Auto Swing Louveri<sup>1</sup>/<sub>4</sub> Optionali<sup>1</sup>/<sub>4</sub>%: i<sup>1</sup>/<sub>4</sub> Optionali<sup>1</sup>/<sub>4</sub>%
- Sleep Operation: Yes
- Smart Function: Yes
- Super Function: Yes
- Compressor Indicator: No
- Auto Restart: Yes

- Dimmer: Yes
- 2 Ways Draining Connection (Left or Right): Yes
- Net Dimensions WxHxD (mm):Indoor Unit: 790x255x200
- Net Dimensions WxHxD (mm):Outdoor Unit: 660×482×240
- Net Weight (Kg):Indoor Unit: 7.3
- Net Weight (Kg):Outdoor Unit: 22.5
- Packing Dimensions WxHxD (mm):Indoor Unit: 850x320x260
- Packing Dimensions WxHxD (mm):Outdoor Unit: 780×530×315
- Gross Weight (Kg):Indoor Unit: 8.5
- Gross Weight (Kg):Outdoor Unit: 25
- Loading Capacity (20'/40'/40'HC))ï<sup>1</sup>/<sub>4</sub>^No pipeï<sup>1</sup>/<sub>4</sub>‰: 158/316/348
- Loading Capacity (20'/40'/40'HC) i<sup>1</sup>/<sub>4</sub>°With pipei<sup>1</sup>/<sub>4</sub>%: 140/280/324
- Test Standard: EN 14511

Date: 2025-02-05 15:23