



## HP LaserJet M440dn MFP Printer

Model No: LPHPPRM440DN



### Price:

---

Rs. 274,990

### Warranty:

---

1 Years(s) manufacturer warranty.  
1 Year Warranty

### Delivery:

---

Delivery - Standard 3 To 5 Working Days.

- Delivery Within 3 Working Days For Colombo And Suburbs, 5 Working Days For Other Locations.
- For Any Invoice Up To Rs.9,999, A Delivery Rate Of Rs.500 Will Be Charged.
- For Any Invoice From Rs.10,000 To 19,999, A Delivery Rate Of Rs.700 Will Be Charged.
- For Any Invoice From Rs.20,000 To 49,999, A Delivery Rate Of Rs.900 Will Be Charged.
- For Any Invoice From Rs.50,000 To 99,999, A Delivery Rate Of Rs.1200 Will Be Charged.
- For Any Invoice From Rs.100,000 To 149,999, A Delivery Rate Of Rs.1500 Will Be Charged.
- For Any Invoice From Rs.150,000 And Above, A Delivery Rate Of Rs.2000 Will Be Charged.

## Specifications:

---

- Functions: Print, copy, scan
- Print speed black (ISO): Up to 24 ppm
- Print speed black (ISO, A4): Up to 24 ppm
- Print speed color (ISO): N/A
- Print speed color (draft, A4): N/A
- Print Speed Color (ISO): N/A
- Duplex printing: Automatic (standard)
- Duty cycle (monthly, letter): Up to 50,000 pages per month
- Duty cycle (monthly, A4): Up to 50,000 pages per month
- Recommended monthly page volume: 2000 to 5000
- Print quality black (best): Up to 1200 x 1200 dpi
- Print languages: PS
- Print technology: Laser
- Connectivity, standard: Hi-Speed USB 2.0 Device, Ethernet 10/100 Base TX
- Wireless capability: No
- Minimum System Requirements: CD-ROM or DVD drive, or Internet connection; dedicated USB or network connection or Wireless connection; 200 MB available hard disk space; (For OS hardware requirements see microsoft.com) for Windows, Pentium IV 2.4GHz (Intel Core™2) / RAM 512 MB (1 GB) / Free HDD space 1 GB (2 GB) for Linux
- Display: 4-line LCD
- Processor speed: 600 MHz
- Memory: 512MB
- Compatible Operating Systems: Windows OS compatible with In-Box Driver; Windows Server 2003/2003R2 32-bit (SP1/SP2) Standard/Enterprise (+ Cluster & Terminal Services), Windows Server 2008 32-/64-bit (SP2) Standard/Enterprise (+ Cluster & Terminal Services), Windows Server 2008 R2 64-bit (SP1) Standard/Enterprise (+ Cluster & Terminal Services; Windows OS compatible with Universal Print Driver (UPD) or Product-Specific drivers from <http://www.hp.com>; Windows Server 2003/2003 R2 32-/64-bit (SP1/SP2) Standard/Enterprise/Datacenter (+ Cluster & Terminal Services), Windows Server 2008/2008 R2 32-/64-bit (SP1/SP2) Standard/Enterprise/Datacenter (+ Cluster & Terminal Services), Windows Server 2012/2012 R2 64-bit Standard/Foundation/Essentials/Datacenter (+ Cluster & Terminal Services) ; Windows 8 (32-bit / 64-bit) recommend v5.86+, 8.1 recommend v5.94+, Windows 7 (32-bit / 64-bit) recommend v5.82+, Windows Vista (32-bit / 64-bit) recommend v5.82+, Windows XP /SP3 (32-bit / 64-bit) recommend v5.82+
- Paper handling input, standard: Tray 1: 100 sheet, Tray 2: 250 sheet
- Paper handling output, standard: Up to 250 Sheets
- Finished output handling: No
- Media types: Plain, Mid-weight, Light, HP LaserJet, Colored, Preprinted, Recycled, Intermediate, Letterhead, Prepunched
- Media sizes supported: A3; A4; A5; A6; B4 (JIS); B5 (JIS); 8K; 16K; O?cio 216x340mm
- Media sizes, custom: Tray 1: 98 x 148 to 297 x 432 mm; Tray 2: 148 x 210 to 297 x 354 mm;

- Borderless printing: N/A
- Media weight, recommended: Tray 1: 60 to 163 g/m<sup>2</sup>; Tray 2: 60 to 110 g/m<sup>2</sup>
- File Format Supported: PDF; JPEG; TIFF
- Scanner type: Flatbed
- Scan file format: PDF, JPEG, TIFF
- Enhanced scanning resolution: Up to 4800 × 4800 dpi
- Scan resolution, optical: Up to 600 dpi
- Scan resolution, hardware: Up to 600 × 600 dpi
- Scan size, maximum: 297 x 432 mm
- Scan technology: Digital-CMOS Image Sensors (D-CIS)
- Copy speed black (ISO): Up to 24 cpm
- Copy resolution (black text): Up to 600 x 600 dpi
- Copies, maximum: Up to 999 copies
- Copier settings: 600 x 600 dpi x 2 bit; Originals content settings: Text, Text/Photo, Photo,Map; Reduce/Enlarge scaling: 25 to 400% ; Copy qty settings: 1 to 999;Darkness controls: 11 levels (Light, Normal, Dark); Collation: Yes (Limited);N-up: A3: 2/4/8/16-up; A4: 2/4/8-up
- Power consumption: 580 watts (Active Printing), 80 watts (Ready) 0.7 watts (Sleep), 0.2 watts(Off)
- Power: AC 220 - 240V: 50/60Hz. Not dual voltage, power supply varies by partnumber with # Option code identifier.
- Operating humidity range: 20 to 80% RH
- Recommended operating humidity range: 20 to 80% RH
- Operating temperature range: 10 to 30°C
- Typical electricity consumption (TEC) number: Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and void the product warranty. Energy Star value typically based on measurement of 230V for Blue Angel.
- Energy star certified: No
- Safety: IEC 60950-1:2005 +A1:2009 +A2:2013 (International), EN 60950-1:2006+A11:2009 +A1:2010 +A12:2011 +A2:2013 (EU), IEC 60825-1:2014,EN60825-1:2014 (Class 1 Laser/LED Device), Low Voltage Directive 2014/35/EU with CE Marking (Europe) GB4943.1-2011; other safety approvals as required by individual countries
- Security management: Embedded Web Server: password protection/encryption, Secure Erase of Client Data, configurable login failure policy, configurable auto logout, Certificate Management, Pre-Shared Key Authentication, Support for WPA10, IPv4/v6/mac address filtering, SMTP server Certificate Validation, Encrypted Customer Data Storage, secure browsing via SSL/TLS, SMTP over SSL/TLS, IPP over SSL/TLS, IPsec, SNMPv3
- Minimum dimensions (W x D x H): 560 x 540 x 417 mm
- Maximum dimensions (W x D x H): 960 mm x 1090 mm x 933 mm
- Weight: 25.4 kg

Date: 2025-04-01 04:40